



Product Specification Sheet

APS290

Rev. 1 - 02/99



234 Surf. Swipe Card Reader + Keypad

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The access control system shall be Alpha Communications®/IEI model 234 keypad or approved equivalent. The keypad memory shall have nonvolatile EEPROM memory for up to 60 users. Codes may be from 1-6 digits in length and digits may be repeated. Any ABA standard track II encoded magnetic stripe card may be programmed as a user. Users may be programmed as card only, code only, card and code or either.

Assisted by the door position sensor input, this 1 amp Form-C relay shall energize if the door is opened without a valid user entry or egress input. This output can be programmed to energize for up to 15 minutes or latch. It can be reset by a valid code/card entry.

The systems propped door relay can be programmed for a 1 to 15 minute time window in which the door may be held open after a valid entry. The system shall alert the resident to any "propped" door by energizing a 1 amp Form 'C' relay. This output may be wired to a siren, buzzer, guard station, camera or any other device.

The lock release relay is rated a 8 amps and shall be tough enough to handle any locking device. Simple programming allows the output to toggle (by code) or time from 1 to 90 seconds.

234 Surface Swipe Card Reader + Keypad

The 234 keypad offers field proven reliability and cost effective solutions for residential, commercial and industrial installations, elegant yet durable, it blends with any decor. Designed for compatibility with any electric locking device. The keypad accept power from any 12-24V AC/DC supply. No separate programmer is ever necessary.

FEATURES

- Lock release relay
- Lock release timer
- Forced door alarm relay and Propped door alarm relay
- Alarm zone shunting relay
- Timed egress input
- 60 user capacity
- Front Programming
- Weather-resistant metal housing
- Uses any ABA standard track II magstripe card
- Access via card, keypad or both

SPECIFICATIONS

MECHANICAL

Dimensions:

Programming Keypad:

Height: 4.50" (114.3mm)

Width: 4.50" (114.3mm)

Depth: 1.55" (39.4mm)

ELECTRICAL

Voltage:

12 to 24 volts AC or DC (selected by jumper)
(Normally used with model SS106 pigtail or model T1240 plug-in transformer)

Current:

@12VDC 20mA typical, 50mA worst case

@24VDC 25mA typical, 70mA worst case

Note:

keypads using additional relays require an additional 15mA for each relay energized.

Outputs:

Main relay: 8 Amp, Form 'C' @24VDC-10 Amp surge

Alarm Zone Shunting Relay: 1 Amp, Form 'C' @24VDC

Forced Door Relay: 1 Amp, Form 'C' @24VDC

Propped Door Relay: 1 Amp, Form 'C' @24VDC

Wire Distance:

250' between reader and electronics with #22AWG

ENVIRONMENTAL

Temperature:

-20°F to 130°F (-28°C to 54°C)

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.

Copyright© 1999-2000, Alpha Communications®, All Rights Reserved