

A desirable sound system begins with a good microphone. Paso unidirectional dynamic microphones' frequency response has been tailored to provide the best possible reproduction regardless of environmental noise, undesirable acoustics and microphone placement. Most Paso "Handlers" series microphones feature a rugged die-cast zinc alloy enclosure. This mechanical solution insures high tensile strength and great resistance to shock. The dynamic element is then surrounded by a heavy-duty woven wire mesh grille and further protected by a foam "pop" and windscreen. Finally the exclusive non-reflecting scratch and stain resistant finish is electroplated on the enclosure for long lasting protection and beauty.

**The PASO Handlers® Unidirectional Dynamic Microphones . . . Quality you can feel !**

**Unidirectional Dynamic Microphones**



**Economy Model M91**

Unidirectional Dynamic  
General Purpose Public Address

**Model Configurations**


- M91F** -With Female Connector\*
- M91M** - With Male Connector\*
- M91P** - With ¼" Gold Plug

\* 3 pin audio connector attached at equipment end

A low cost, general purpose Unidirectional Dynamic Microphone that offers good quality in a handsomely designed ABS enclosure. The high sensitivity cartridge is shock mounted to minimize handling noise and protection against jarring. Ideal for public address applications the cardioid pattern is particularly useful in the cancelling of acoustic feedback and unwanted background noise. The frequency response is tailored to provide a crisp and clear reproduction without annoying boominess. Other characteristics include metal wind screen, On Off switch, non-reflecting scratch resistant matte black finish, standard mount stand holder and 15 ft. cable (Attached).

- Low Impedance
- Stand Holder
- 15 ft. Cable
- On-Off Switch
- Shock Mounted
- Black Satin Finish

**Element:** Dynamic Shock Mounted  
**Frequency Response:** 60 - 13,000 Hz  
**Polar Pattern:** Cardioid  
**Impedance:** 250 ohm  
**Output Level:** At 1,000 Hz  
**Power Level:** -55db (0db=1 mw/10 mbar)  
**Open Circuit Voltage:** -74db 0.20 mV (0db=1 V/mbar)  
**Switch:** On- Off  
**Case:** ABS  
**Finish:** Matte Black  
**Dimensions:** 8.7" (220 mm) High  
 2" (52 mm) head diameter  
**Accessories Included:** Tapered Stand Holder 5/8"-27  
**Cable:** 15 ft. (5 m) attached  
**Net Weight:** 12 oz (340 gr.) with cable



Frequency in Hertz



**High Output M911**

Unidirectional Dynamic  
General Purpose Public Address

**Model Configurations**


- M911F** -With Female Connector\*
- M911M** - With Male Connector\*
- M911X** - Without Connector

\* 3 pin audio connector attached at equipment end

A general purpose Unidirectional Dynamic Microphone that offers good quality in a handsomely designed enclosure. The high sensitivity and high output cartridge is shock mounted to minimize handling noise. Specifically designed for voice applications the uni pattern is particularly useful for cancelling acoustic feedback and background noise. The smooth response is tailored to provide a crisp and clear reproduction without annoying boominess. Other characteristics include rugged wimerech wind screen, On Off switch, non-reflecting scratch resistant black electroplated finish, standard mount stand holder, 15 ft. cable and protective carrying case.

- Low Impedance
- Stand Holder
- Detachable Cable
- On-Off Switch
- Shock Mounted
- Black Satin Finish

**Element:** Dynamic Shock Mounted  
**Frequency Response:** 60 - 14,000 Hz  
**Polar Pattern:** Cardioid  
**Impedance:** 250 ohm  
**Output Level:** At 1,000 Hz  
**Power Level:** -55 db (0 db=1 mw/10 mbar)  
**Open Circuit Voltage:** -74 db .20 mV (0 db=1 V/mbar)  
**Switch:** On- Off  
**Case:** Zinc Diecast  
**Finish:** Matte Black  
**Dimensions:** 6.5" (165 mm) Long  
 2.15" (54 mm) head diam.  
**Accessories Included:** Tapered Stand Holder 5/8"-27  
 15 Ft. (5 m) Cable, Carrying Case  
**Net Weight:** 11 oz (312 grams)



Frequency in Hertz



**High Output M921**

Unidirectional Dynamic  
General Purpose Public Address

**Model Configurations**


- M921F** -With Female Connector\*
- M921M** - With Male Connector\*
- M921X** - Without Connector

\* 3 pin audio connector attached at equipment end

A general purpose, Unidirectional Dynamic Microphone particularly suited for sound reinforcement and recording. The rugged high sensitivity and high output cartridge is shock mounted to minimize handling noise. Specifically designed for voice applications the uni pattern is particularly useful for cancelling acoustic feedback and unwanted background noise. The smooth response is tailored to provide a crisp and clear reproduction without annoying boominess. Other characteristics include metal wind screen, On Off switch, matte black non-reflecting scratch and stain resistant electroplated finish, standard mount stand holder and a 15 ft. detachable cable.

- Low Impedance
- Stand Holder
- Detachable Cable
- On-Off Switch
- Shock Mounted
- Black Satin Finish

**Element:** Dynamic Shock Mounted  
**Frequency Response:** 60 - 15,000 Hz  
**Polar Pattern:** Cardioid  
**Impedance:** 250 ohm  
**Output Level:** At 1,000 Hz  
**Power Level:** -55 db (0 db=1 mw/10 mbar)  
**Open Circuit Voltage:** -74 db .20 mV (0 db=1 V/mbar)  
**Switch:** On- Off  
**Case:** Zinc Diecast  
**Finish:** Matte Black  
**Dimensions:** 6.5" (165 mm) long  
 1.6" (40 mm) head diameter  
**Accessories Included:** Stand Holder 5/8"-27  
 15 Ft. (5 m) Cable, Carrying Case  
**Net Weight:** 11 oz (312 grams)



Frequency in Hertz